



# DRY VAN TRAILER



Choose from the options below to generate a customized order number.

SES952 -

**DRY VAN TYPE**

- Straight
- Step Deck

**MAX LENGTH**

- Minimum Amount Required
- Custom Length (29 ft - 48 ft)
- Requested Length (ft)

**MAX HEIGHT**

- Standard 13' 6"
- Custom 12' 6"

**INSTALLED EQUIPMENT TYPE**

- SES320 Conditioning System
- SES320R Conditioning & Regeneration System

**GENERATOR(s)** (SEE GENERATOR PN MATRIX)

- None
- Primary- Full Load Diesel Tier IVF-Tow behind
- Secondary Only
- Primary & Secondary

**ISOLATED CONTROL & LAB AREA**

- None
- 96" Min w/ side door & clear observation sliding partition
- 96" Min w/ side door, solid wall partition, & hinged man door

**ISOLATED STORAGE AREA**

- None
- Yes w/ solid room partition access door
- Yes w/ solid partition and curbside exterior man door

**OIL CONNECTIONS**

- Dual Rear
- Dual Exterior Belly Mounted both sides
- Dual Exterior Belly Mounted w/ Enclosures both sides

**VACUUM CONNECTIONS**

- None
- Single - Interior Rear
- Dual - Interior Upper Side Wall
- Dual - Exterior Belly Mounted both sides
- Dual - Exterior Belly Mounted w/ Enclosures both sides

**SIDE MAN DOOR**

- 304 SS exterior door & frame w/ observation window & SS lockset
- FRP door w/ exterior cam lock & interior latch & observation window

**CONTROL AREA SIDE ENTRY**

- None
- Aluminum stairs with single removable railing
- Aluminum stairs with dual removable railings
- Belly mounted pull out landing w/ removable stair & railing assemblies

**ADDITIONAL ENTRY STAIRS**

- None
- Aluminum stairs per control area railing arrangement (rear only)
- Aluminum stairs per control area railing arrangement (all entry doors)

**BELLY STAIR STORAGE**

- None
- Lockable aluminum belly mounted dual stairs storage assembly

**SIDE WINDOWS**

- None
- Control room roadside observation window
- Equipment area egress window (rear door access)

**VENTILATION**

- Factory standard
- Power intake louvers

**INTERIOR LIGHTING PACKAGE**

- None
- Area LED ceiling mounted lighting with individual load center control
- Area LED ceiling mounted lighting with wall switch control

**EXTERIOR LIGHTING PACKAGE**

- None
- Curbside & Driverside Flush Mount LED Flood Lights with dual load center control (2 lights)
- Area LED ceiling mounted lighting with individual load center control (4 lights)

**INTERIOR 120V/1 PACKAGE**

- None
- STD PKG - 15A GFCI Outlets Equipment area (4), Control area (6), Front area (4)
- STD PKG plus two additional dedicated 15A GFCI appliance outlets

**EXTERIOR 120V/1 PACKAGE**

- None
- Curbside & Driverside GFCI Receptacles (2)

**AREA HEATING**

- None
- Control area 5 kW ceiling forced air heater w/ wall thermostat
- Control & Equipment are 5 kW ceiling forced air heaters w/ wall thermostats

**AREA COOLING**

- None
- Wall mounted 18k BTU A/C
- Exterior nose mounted commercial duty 24k BTU A/C

**LOOSE HOSE STORAGE**

- None
- Skid intergraded vacuum & oil straight length hose storage. (100 ft 4" vacuum hose, 160 ft 2" oil hose)
- Full width belly compartment vacuum and oil hose storage

**POWER CABLE PROVISIONS**

- None
- (4) conductor 15 ft pigtail / 50 ft cable set with high amperage quick connectors w/ access door
- (4) conductor exterior high amperage twist lock connection box & 50 ft cable set w/ mating twist connectors

**BELLY STORAGE**

- None
- Propose belly storage to fit the available space

**CONTROL AREA FURNITURE**

- None
- Propose control area furniture to fit the available space

**WASTE OIL STORAGE TANK**

- None
- 40 gallon aluminum belly mounted waste oil tank w/ exterior level gauge & 3" fill connection

**BELLY PULL OUT TABLE**

- None
- 48 x 36" pull out aluminum work table w/ lower storage drawer assembly

**TESTING POWER SUPPLIES**

- None
- 230V / 3φ - 30A - with receptacle and 50 ft cable
- 230V / 1φ - 30A - with receptacle and 50 ft cable
- Both

Name :

E-mail :

Phone :

Company :

Please save the completed worksheet and send it back either through E-mail or fax using the contact information below.